

Reolink TrackMix LTE

4G LTE Dual-Lens Camera with Auto-Zoom Tracking

- Dual-View Display
- Auto-Zoom Tracking
- 4G LTE Network

Specifications

Video & Audio	
Image Sensor	1/3"CMOS Sensor
Video Resolution	Up to 3840×2160 (8.0 Megapixels) at 15 frames/sec
Lens	f=2.8mm@F=1.6 , f=8mm@F=1.6
Video Compression	H.264,H.265
Field of View	<ul style="list-style-type: none"> • Horizontal: 96°-38° • Vertical: 55°-21°
Zoom Mode	6X hybrid zoom
Day & Night	IR-cut filter with auto-switching
Infrared Night Vision	Up to 30 Meters (100ft)(LED: 2pcs/850nm)
Color Night Vision	Spotlight: 1pcs/6500K/450 Lumens
Audio	Two-way audio
Power	
Battery	7.2V 5100mAh rechargeable battery (Battery life varies based on settings, usage & temperature) 36.72Wh(Power capacity)

Solar	Reolink Solar Panel 2
DC Power	5V/2A
Interface	
Power	USB Type-C port
System	Reset button
Storage	Micro SD card slot (max. 128GB)
Audio	Built-in microphone and speaker
Pan & Tilt	
Pan &Tilt	Pan: 355°, Tilt: 0°~90°; (Speed can be set)
Preset Points	32
Auto Tracking	Support
3G/4G Bandwidth	
Frequency Bands	Europe version: LTE FDD: B1/B3/B7/B8/B20/B28A WCDMA: B1/B8" "USA version: LTE FDD: B2/B4/B5/B12/B13/B14/B66/B71" "Australia version: LTE FDD: B1/B3/B5/B7/B8/B28 WCDMA: B1/B5/B8
Transmission Data	LTE FDD: Max 10Mbps(DL), Max 5Mbps(UL) LTE TDD: Max 8.96Mbps(DL), Max 3.1Mbps(UL) HSPA+: Max 42Mbps(DL), Max 5.76Mbps(UL) UMTS: Max 384Kbps(DL), Max 384Kbps(UL)
Software Features	
Frame Rate	<ul style="list-style-type: none"> • Mainstream: 10fps - 15fps • Substream: 10fps - 15fps
Code Rate	<ul style="list-style-type: none"> • Mainstream: 1024Kbps -4096Kbps • Substream: 64Kbps -512Kbps
OS Supported	PC: Windows, Mac OS; Smartphone: iOS, Android
Smart Alarm	PIR detection/person detection/vehicle detection/pet detection
Record Mode	Motion-triggered recording

Protocols & Standards	SSL, TCP/IP, UDP, UPNP, SMTP, NTP, P2P
Maximum User Access	Support up to 12 simultaneous video streams (10 substreams & 2 mainstreams)
Work with	Google Assistant, Reolink Cloud
Working Environment	
Operating Temperature	-10°C~+55°C (14°F~131°F)
Operating Humidity	20% ~ 85%
Weatherproof	IP65
Size & Weight	
Dimensions	228.2*147*129mm
Weight	1.4KG
Warranty	
Limited Warranty	2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/

Gallery & Specs



1. Spotlight
2. Infrared LED
3. Lens
4. Mic
5. Daylight Sensor
6. PIR Sensor



1. Micro SD Card Slot

